

# TECHNICAL DATA MANUAL

OPTIMUS PRO Mono  
ATW Heat Pump



**IMPORTANT NOTE:**

Thank you very much for purchasing our product,  
Before using your unit , please read this manual carefully and keep it for future reference.



## Product fiche 1

Heat pump space heater		unit	MONO18W/MONO3	MONO22W/MONO3	MONO26W/MONO3	MONO30W/MONO3
Indoor unit sound power (*)		[dB(A)]	/	/	/	/
Outdoor unit sound power (*)		[dB(A)]	71	73	75	77
Capacity of the back-up heater integrated in the unit		[kW]	0	0	0	0
Psup back-up heater		[kW]	No	No	No	No
off peak operation function integrated in Heat pump		Y/N	No	No	No	No
Space heating		Energy efficiency class 35°C (Low temp. app.)	A+++	A+++	A+++	A++
Space heating		Energy efficiency class 55°C (Medium temp. app.)	A++	A++	A+	A+
Average climate (Design temperature= -10°C)						
Prated(declared heating capacity) @-10°C		[kW]	18	22	25	29
Space heating 35°C		Seasonal space heating efficiency(ηs)	181	178	177	165
		Annual energy consumption	8,086	10,180	11,489	14,165
Prated(declared heating capacity) @-10°C		[kW]	18	22	26	30
Space heating 55°C		Seasonal space heating efficiency(ηs)	125	126	123	123
		Annual energy consumption	11,375	14,390	17,204	19,316
Part load conditions space heating average climate low temperature application						
Pdh(declared heating capacity)		[kW]	15.91	19.73	22.15	21.95
(A) condition (-7°C)		COPd (declared COP)	2.85	2.74	2.56	2.53
		Cdh(degradation coefficient)	0.90	0.90	0.90	0.90
Pdh(declared heating capacity)		[kW]	9.67	12.04	13.78	16.22
(B) condition (2°C)		COPd (declared COP)	4.57	4.40	4.41	4.12
		Cdh(degradation coefficient)	0.90	0.90	0.90	0.90
Pdh(declared heating capacity)		[kW]	6.57	8.02	9.38	10.69
(C) condition (7°C)		COPd (declared COP)	5.95	6.24	6.43	6.21
		Cdh(degradation coefficient)	0.90	0.90	0.90	0.90
Pdh(declared heating capacity)		[kW]	3.77	3.81	4.11	4.59
(D) condition (12°C)		COPd (declared COP)	6.97	7.0	7.08	7.14
		Cdh(degradation coefficient)	0.90	0.90	0.90	0.90

**Product fiche 2**

Heat pump space heater		unit	MONO18WMONO3	MONO22WMONO3	MONO26WMONO3	MONO30WMONO3
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-10	-10	-10	-10
	Pdh (declared heating capacity)	[kW]	18.14	20.34	20.36	20.43
	COPd (declared COP)	-	2.49	2.35	2.34	2.34
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
(F) Tbivalent temperature	Tbiv	[°C]	-7	-7	-7	-5
	Pdh (declared heating capacity)	[kW]	15.91	19.73	22.15	23.57
	COPd (declared COP)	-	2.85	2.74	2.56	2.70
Supplementary capacity at P_design	Psup (@Tdesign:-10°C)	[kW]	0.00	1.97	4.68	8.75
<b>Part load conditions space heating average climate medium temperature application</b>						
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	15.64	19.84	20.65	20.12
	COPd (declared COP)	-	1.72	1.74	1.69	1.63
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	9.62	11.91	14.28	16.50
(B) condition (2°C)	COPd (declared COP)	-	3.30	3.30	3.11	3.09
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	6.40	7.99	9.30	10.51
(C) condition (7°C)	COPd (declared COP)	-	4.41	4.62	4.72	4.73
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	3.60	3.62	3.90	4.65
	COPd (declared COP)	-	5.09	5.20	5.41	5.85
(D) condition (12°C)	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Tol (temperature operating limit)	[°C]	-10	-10	-10	-10
	Pdh (declared heating capacity)	[kW]	15.03	13.83	13.87	13.83
	COPd (declared COP)	-	1.17	1.08	1.08	1.07
(E) Tol(temperature operating limit)	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
	Tbiv	[°C]	-7	-7	-6	-5
	Pdh (declared heating capacity)	[kW]	15.64	19.84	22.13	23.98
	COPd (declared COP)	-	1.72	1.74	1.88	2.02
Supplementary capacity at P_design	Psup (@Tdesign:-10°C)	[kW]	2.64	8.6	12.28	15.86

**Product fiche 3**

Heat pump space heater		unit	MONO18WMONO3	MONO22WMONO3	MONO26WMONO3	MONO30WMONO3
Colder climate (Design temperature = -22°C)						
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	18	21	26	29
	Seasonal space heating efficiency (ηs)	[%]	146	146	143	138
	Annual energy consumption	[kWh]	11,740	14,179	17,421	20,390
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	97	102	101	100
	Annual energy consumption	[kWh]	18,156	21,067	24,967	29,238
Part load conditions space heating colder climate low temperature application						
condition (-15°C)	Pdh (declared heating capacity)	[kW]	14.49	17.46	18.95	18.61
	COPd (declared COP)	-	2.42	2.36	2.27	2.24
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	11.21	13.30	15.91	18.49
	COPd (declared COP)	-	3.09	3.12	3.10	3.07
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.64	8.25	10.10	11.88
	COPd (declared COP)	-	4.50	4.42	4.45	4.42
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.77	5.45	6.30	7.53
	COPd (declared COP)	-	5.85	5.87	6.06	6.15
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.95	3.98	4.03	4.11
	COPd (declared COP)	-	7.18	7.19	7.13	6.87
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-22	-22	-22	-22
	Pdh (declared heating capacity)	[kW]	13.14	13.27	13.07	13.17
	COPd (declared COP)	-	1.67	1.69	1.67	1.67
(F) Tbivalent temperature	WTOL (Heating water Operation Limit)	[°C]	37	37	37	37
	Tbiv	[°C]	-15	-15	-12	-10
	Pdh (declared heating capacity)	[kW]	14.49	17.46	18.97	19.93
Supplementary capacity at P_design	COPd (declared COP)	-	2.42	2.36	2.36	2.44
	Psup (@Tdesign:-22°C)	[kW]	4.62	8.13	12.68	15.96

**Product fiche 4**

Heat pump space heater		unit	MONO18WMONO3	MONO22WMONO3	MONO26WMONO3	MONO30WMONO3
Part load conditions space heating colder climate medium temperature application						
condition (-15°C)	Pdh (declared heating capacity)	[kW]	13.56	13.78	13.37	13.06
	COPd (declared COP)	-	1.21	1.24	1.20	1.18
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	11.12	13.53	15.90	18.40
	COPd (declared COP)	-	1.98	2.07	2.10	2.10
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.65	8.61	10.17	11.23
	COPd (declared COP)	-	3.44	3.70	3.58	3.51
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.66	5.21	6.52	7.42
	COPd (declared COP)	-	4.35	4.49	4.99	5.18
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.74	3.74	3.63	3.64
	COPd (declared COP)	-	5.68	5.76	5.68	5.73
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) ToI (temperature operating limit)	ToI (temperature operating limit)	[°C]	-15	-15	-15	-15
	Pdh (declared heating capacity)	[kW]	13.56	13.78	13.37	13.06
	COPd (declared COP)	-	1.21	1.24	1.20	1.18
(F) TbiValent temperature	WTOL (Heating water Operation Limit)	[°C]	50	50	50	50
	Tbiv	[°C]	-7	-7	-7	-7
	Pdh (declared heating capacity)	[kW]	11.12	13.53	15.90	18.40
Supplementary capacity at P_design	COPd (declared COP)	-	1.98	2.07	2.10	2.10
Warmer climate (Design temperature =2°C)	P_sup (@Tdesign:-22°C)	[kW]	18.38	22.36	26.27	30.41
Space heating 35°C						
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	226	234	231	213
	Annual energy consumption	[kWh]	4,116	4,945	5,959	7,540
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	157	161	168	163
	Annual energy consumption	[kWh]	6,041	7,180	8,218	9,580

**Product fiche 5**

Heat pump space heater		unit	MONO18WMONO3	MONO22WMONO3	MONO26WMONO3	MONO30WMONO3
Part load conditions space heating warmer climate low temperature application						
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	17.84	21.81	25.50	26.29
	COPd (declared COP)	-	3.53	3.31	3.0	2.94
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	11.36	14.08	16.77	19.57
	COPd (declared COP)	-	5.16	5.20	5.02	4.75
(C) condition (7°C)	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	5.45	6.44	7.65	8.90
(D) condition (12°C)	COPd (declared COP)	-	7.01	7.50	7.78	7.53
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) ToI(temperature operating limit)	ToI (temperature operating limit)	[°C]	2	2	2	2
	Pdh (declared heating capacity)	[kW]	17.84	21.81	25.50	26.29
	COPd (declared COP)	-	3.53	3.31	3.0	2.94
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
	Tbiv	[°C]	7	7	7	7
(F) Tbivalent temperature	Pdh (declared heating capacity)	[kW]	11.36	14.08	16.77	19.57
	COPd (declared COP)	-	5.16	5.20	5.02	4.75
Supplementary capacity at P <sub>design</sub>	Psup (@Tdesign:2°C)	[kW]	0.00	0.09	0.58	4.15
Part load conditions space heating warmer climate medium temperature application						
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	18.44	22.12	26.50	26.41
	COPd (declared COP)	-	2.12	2.12	1.99	1.99
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	11.62	14.15	16.86	19.11
	COPd (declared COP)	-	3.49	3.50	3.47	3.37
(C) condition (7°C)	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	5.35	6.38	7.58	8.92
(D) condition (12°C)	COPd (declared COP)	-	5.09	5.34	5.94	6.09
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) ToI(temperature operating limit)	ToI (temperature operating limit)	[°C]	2	2	2	2
	Pdh (declared heating capacity)	[kW]	18.44	22.12	26.50	26.41
	COPd (declared COP)	-	2.12	2.12	1.99	1.99
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60

## Product fiche 6

Heat pump space heater		unit	MONO18WMONO3	MONO22WMONO3	MONO26WMONO3	MONO30WMONO3
(F) T <sub>biv</sub> temperature	T <sub>biv</sub>	[°C]	7	7	7	7
	P <sub>dh</sub> (declared heating capacity)	[kW]	11.62	14.15	16.86	19.11
	COP <sub>d</sub> (declared COP)	-	3.49	3.50	3.47	3.37
Supplementary capacity at P <sub>design</sub>	P <sub>sup</sub> (@T <sub>design</sub> :2°C)	[kW]	0.00	0.00	0.00	3.32
Ecodesign technical data						
Product description	Air-to-water heat pump	Y/N	Yes	Yes	Yes	Yes
	Water-to-water heat pump	Y/N	No	No	No	No
	Brine-to-water heat pump	Y/N	No	No	No	No
	Low-temperature heat pump	Y/N	No	No	No	No
	Equipped with a supplementary heater	Y/N	No	No	No	Yes
Air to water unit	Heat pump combination heater	Y/N	No	No	No	No
	Rated airflow (outdoor)	[m <sup>3</sup> /h]	10650	10650	11200	11200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m <sup>3</sup> /h]	/	/	/	/
Other	Capacity control	-	Inverter	Inverter	Inverter	Inverter
	P <sub>off</sub> (Power consumption Off mode)	[kW]	0.018	0.018	0.018	0.018
	P <sub>to</sub> (Power consumption Thermostat off mode)	[kW]	0.096	0.096	0.096	0.096
	P <sub>sb</sub> (Power consumption Standby mode)	[kW]	0.018	0.018	0.018	0.018
	P <sub>CK</sub> (Power crankcase heater model)	[kW]	0.000	0.000	0.000	0.000
	Q <sub>elec</sub> (Daily electricity consumption)	[kWh]	/	/	/	/
	Q <sub>fuel</sub> (Daily fuel consumption)	[kWh]	/	/	/	/

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.



## Technical parameters

Model(s):	MONO18WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	17.7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	15.6	kW
Tj = 2 °C	Pdh	9.6	kW
Tj = 7 °C	Pdh	6.4	kW
Tj = 12 °C	Pdh	3.6	kW
Tj = bivalent temperature	Pdh	15.6	kW
Tj = operating limit	Pdh	15.0	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-71	dB
Annual energy consumption	Q <sub>HE</sub>	11375	kWh

For heat pump combination heater:

Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	125	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.72	-
Tj = 2 °C	COP <sub>d</sub>	3.30	-
Tj = 7 °C	COP <sub>d</sub>	4.41	-
Tj = 12 °C	COP <sub>d</sub>	5.09	-
Tj = bivalent temperature	COP <sub>d</sub>	1.72	-
Tj = operating limit	COP <sub>d</sub>	1.17	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	2.6	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO18WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	COLDER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	18.4	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	11.1	kW
Tj = 2 °C	Pdh	6.7	kW
Tj = 7 °C	Pdh	4.7	kW
Tj = 12 °C	Pdh	3.7	kW
Tj = bivalent temperature	Pdh	11.1	kW
Tj = operating limit	Pdh	13.6	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	13.6	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-71	dB
Annual energy consumption	Q <sub>HE</sub>	18156	kWh

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	97	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.98	-
Tj = 2 °C	COP <sub>d</sub>	3.44	-
Tj = 7 °C	COP <sub>d</sub>	4.35	-
Tj = 12 °C	COP <sub>d</sub>	5.68	-
Tj = bivalent temperature	COP <sub>d</sub>	1.98	-
Tj = operating limit	COP <sub>d</sub>	1.21	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	1.21	-
For air-to-water heat pumps: Operation limit temperature	TOL	-15	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	50	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	18.4	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO18WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	18.1	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	18.4	kW
Tj = 7 °C	Pdh	11.6	kW
Tj = 12 °C	Pdh	5.4	kW
Tj = bivalent temperature	Pdh	11.6	kW
Tj = operating limit	Pdh	18.4	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-71	dB
Annual energy consumption	Q <sub>HE</sub>	6041	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	157	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	-	-
Tj = 2 °C	COP <sub>d</sub>	2.12	-
Tj = 7 °C	COP <sub>d</sub>	3.49	-
Tj = 12 °C	COP <sub>d</sub>	5.09	-
Tj = bivalent temperature	COP <sub>d</sub>	3.49	-
Tj = operating limit	COP <sub>d</sub>	2.12	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP <sub>cy</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	0.0	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-						
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Water heating energy efficiency	η <sub>wh</sub>	-	%
Annual electricity consumption	AEC	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
				Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO22WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	22.4	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	19.8	kW
Tj = 2 °C	Pdh	11.9	kW
Tj = 7 °C	Pdh	8.0	kW
Tj = 12 °C	Pdh	3.6	kW
Tj = bivalent temperature	Pdh	19.8	kW
Tj = operating limit	Pdh	13.8	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-73	dB
Annual energy consumption	Q <sub>HE</sub>	14390	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	126	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.74	-
Tj = 2 °C	COP <sub>d</sub>	3.30	-
Tj = 7 °C	COP <sub>d</sub>	4.62	-
Tj = 12 °C	COP <sub>d</sub>	5.20	-
Tj = bivalent temperature	COP <sub>d</sub>	1.74	-
Tj = operating limit	COP <sub>d</sub>	1.08	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	8.6	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-						
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Water heating energy efficiency	η <sub>wh</sub>	-	%
Annual electricity consumption	AEC	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
				Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO22WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	COLDER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	22.4	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	13.5	kW
Tj = 2 °C	Pdh	8.6	kW
Tj = 7 °C	Pdh	5.2	kW
Tj = 12 °C	Pdh	3.7	kW
Tj = bivalent temperature	Pdh	13.5	kW
Tj = operating limit	Pdh	13.8	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	13.8	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-73	dB
Annual energy consumption	Q <sub>HE</sub>	21067	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	102	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	2.07	-
Tj = 2 °C	COP <sub>d</sub>	3.70	-
Tj = 7 °C	COP <sub>d</sub>	4.49	-
Tj = 12 °C	COP <sub>d</sub>	5.76	-
Tj = bivalent temperature	COP <sub>d</sub>	2.07	-
Tj = operating limit	COP <sub>d</sub>	1.24	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	1.24	-
For air-to-water heat pumps: Operation limit temperature	TOL	-15	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	50	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	22.4	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details	NØRDIS AC, Europe www.nordis-ac.com/
-----------------	---

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO22WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	22.0	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	22.1	kW
Tj = 7 °C	Pdh	14.1	kW
Tj = 12 °C	Pdh	6.4	kW
Tj = bivalent temperature	Pdh	14.1	kW
Tj = operating limit	Pdh	22.1	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-73	dB
Annual energy consumption	Q <sub>HE</sub>	7180	kWh

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	161	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	-	-
Tj = 2 °C	COP <sub>d</sub>	2.12	-
Tj = 7 °C	COP <sub>d</sub>	3.50	-
Tj = 12 °C	COP <sub>d</sub>	5.34	-
Tj = bivalent temperature	COP <sub>d</sub>	3.50	-
Tj = operating limit	COP <sub>d</sub>	2.12	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	0.0	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO26WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	26.1	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	20.6	kW
Tj = 2 °C	Pdh	14.3	kW
Tj = 7 °C	Pdh	9.3	kW
Tj = 12 °C	Pdh	3.9	kW
Tj = bivalent temperature	Pdh	22.1	kW
Tj = operating limit	Pdh	13.8	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	-6	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-75	dB
Annual energy consumption	Q <sub>HE</sub>	17204	kWh

For heat pump combination heater:

Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	123	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.69	-
Tj = 2 °C	COP <sub>d</sub>	3.11	-
Tj = 7 °C	COP <sub>d</sub>	4.72	-
Tj = 12 °C	COP <sub>d</sub>	5.41	-
Tj = bivalent temperature	COP <sub>d</sub>	1.88	-
Tj = operating limit	COP <sub>d</sub>	1.08	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	12.3	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

Contact details	NØRDIS AC, Europe www.nordis-ac.com/
-----------------	---

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
 (\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO26WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	COLDER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	26.3	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	15.9	kW
Tj = 2 °C	Pdh	10.2	kW
Tj = 7 °C	Pdh	6.5	kW
Tj = 12 °C	Pdh	3.6	kW
Tj = bivalent temperature	Pdh	15.9	kW
Tj = operating limit	Pdh	13.4	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	13.4	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW
Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-75	dB
Annual energy consumption	Q <sub>HE</sub>	24967	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	101	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	2.10	-
Tj = 2 °C	COP <sub>d</sub>	3.58	-
Tj = 7 °C	COP <sub>d</sub>	4.99	-
Tj = 12 °C	COP <sub>d</sub>	5.68	-
Tj = bivalent temperature	COP <sub>d</sub>	2.10	-
Tj = operating limit	COP <sub>d</sub>	1.20	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	1.20	-
For air-to-water heat pumps: Operation limit temperature	TOL	-15	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	50	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	26.3	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh
Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.



## Technical parameters

Model(s):	MONO26WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	26.2	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	26.5	kW
Tj = 7 °C	Pdh	16.9	kW
Tj = 12 °C	Pdh	7.6	kW
Tj = bivalent temperature	Pdh	16.9	kW
Tj = operating limit	Pdh	26.5	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-75	dB
Annual energy consumption	Q <sub>HE</sub>	8218	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	168	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	-	-
Tj = 2 °C	COPd	1.99	-
Tj = 7 °C	COPd	3.47	-
Tj = 12 °C	COPd	5.94	-
Tj = bivalent temperature	COPd	3.47	-
Tj = operating limit	COPd	1.99	-
For air-to-water heat pumps: Tj = -15 °C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP <sub>cy</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	0.0	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-						
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Water heating energy efficiency	η <sub>wh</sub>	-	%
Annual electricity consumption	AEC	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
				Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO30WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	29.7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	20.1	kW
Tj = 2 °C	Pdh	16.5	kW
Tj = 7 °C	Pdh	10.5	kW
Tj = 12 °C	Pdh	4.7	kW
Tj = bivalent temperature	Pdh	24.0	kW
Tj = operating limit	Pdh	13.8	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	-5	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW
Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-77	dB
Annual energy consumption	Q <sub>HE</sub>	19316	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	123	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.63	-
Tj = 2 °C	COP <sub>d</sub>	3.09	-
Tj = 7 °C	COP <sub>d</sub>	4.73	-
Tj = 12 °C	COP <sub>d</sub>	5.85	-
Tj = bivalent temperature	COP <sub>d</sub>	2.02	-
Tj = operating limit	COP <sub>d</sub>	1.07	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	15.9	kW
Type of energy input	Electrical Heating		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m³/h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh
Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO30WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	COLDER
Parameters are declared for medium-temperature application.	

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	30.4	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	18.4	kW
Tj = 2 °C	Pdh	11.2	kW
Tj = 7 °C	Pdh	7.4	kW
Tj = 12 °C	Pdh	3.6	kW
Tj = bivalent temperature	Pdh	18.4	kW
Tj = operating limit	Pdh	13.1	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	13.1	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-77	dB
Annual energy consumption	Q <sub>HE</sub>	29238	kWh

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q <sub>elec</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	100	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	2.10	-
Tj = 2 °C	COP <sub>d</sub>	3.51	-
Tj = 7 °C	COP <sub>d</sub>	5.18	-
Tj = 12 °C	COP <sub>d</sub>	5.73	-
Tj = bivalent temperature	COP <sub>d</sub>	2.10	-
Tj = operating limit	COP <sub>d</sub>	1.18	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	1.18	-
For air-to-water heat pumps: Operation limit temperature	TOL	-15	°C
Cycling interval efficiency	COP <sub>cyh</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	50	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	30.4	kW
Type of energy input	Electrical Heating		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details: NØRDIS AC, Europe  
www.nordis-ac.com/

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

## Technical parameters

Model(s):	MONO30WMONO3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER
Parameters are declared for medium-temperature application.	

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	29.7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	26.4	kW
Tj = 7 °C	Pdh	19.1	kW
Tj = 12 °C	Pdh	8.9	kW
Tj = bivalent temperature	Pdh	19.1	kW
Tj = operating limit	Pdh	26.4	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	7	°C
Cycling interval capacity for heating	P <sub>cyh</sub>	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.018	kW
Standby mode	P <sub>sb</sub>	0.018	kW
Thermostat-off mode	P <sub>to</sub>	0.096	kW
Crankcase heater mode	P <sub>ck</sub>	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	-77	dB
Annual energy consumption	Q <sub>HE</sub>	9580	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	163	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	-	-
Tj = 2 °C	COPd	1.99	-
Tj = 7 °C	COPd	3.37	-
Tj = 12 °C	COPd	6.09	-
Tj = bivalent temperature	COPd	3.37	-
Tj = operating limit	COPd	1.99	-
For air-to-water heat pumps: Tj = -15 °C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP <sub>cy</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	3.3	kW
Type of energy input	Electrical Heating		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	11200	m <sup>3</sup> /h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details	NØRDIS AC, Europe www.nordis-ac.com/
-----------------	---

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).  
(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

# Information requirements for comfort chillers

Model(s):	MONO18WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	16.6	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	185	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	16.6	kW	$T_j=+35^\circ\text{C}$	$EER_d$	3.06	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	11.9	kW	$T_j=+30^\circ\text{C}$	$EER_d$	4.13	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	7.6	kW	$T_j=+25^\circ\text{C}$	$EER_d$	5.59	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	3.5	kW	$T_j=+20^\circ\text{C}$	$EER_d$	5.55	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	8100	$\text{m}^3/\text{h}$
Sound power level, indoors / outdoors	LWA	-71	dB				
Emissions of nitrogen oxides (if applicable)	$\text{NO}_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	$\text{m}^3/\text{h}$
GWP of the refrigerant	-	675	kg $\text{CO}_2$ eq (100years)				
Standard rating conditions used	Low temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO18WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	18.4	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	216	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	18.4	kW	$T_j=+35^\circ\text{C}$	$EER_d$	4.44	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	13.3	kW	$T_j=+30^\circ\text{C}$	$EER_d$	5.26	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	8.5	kW	$T_j=+25^\circ\text{C}$	$EER_d$	6.68	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	3.3	kW	$T_j=+20^\circ\text{C}$	$EER_d$	5.15	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	8100	m <sup>3</sup> /h
Sound power level, indoors / outdoors	LWA	-/71	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m <sup>3</sup> /h
GWP of the refrigerant	-	675	kg CO <sub>2</sub> eq (100years)				
Standard rating conditions used	Medium temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO22WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	20.6	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	185	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	20.6	kW	$T_j=+35^\circ\text{C}$	$EER_d$	2.89	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	14.9	kW	$T_j=+30^\circ\text{C}$	$EER_d$	3.95	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	9.3	kW	$T_j=+25^\circ\text{C}$	$EER_d$	5.37	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	4.3	kW	$T_j=+20^\circ\text{C}$	$EER_d$	6.19	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	8950	$\text{m}^3/\text{h}$
Sound power level, indoors / outdoors	$L_{WA}$	-/73	dB				
Emissions of nitrogen oxides (if applicable)	$\text{NO}_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	$\text{m}^3/\text{h}$
GWP of the refrigerant	-	675	kg $\text{CO}_2$ eq (100years)				
Standard rating conditions used	Low temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO22WMONO3
Outdoor side heat exchanger of chiller:	Air to water
Indoor side heat exchanger chiller:	Water
Type:	Compressor driven vapour compression
Driver of compressor:	Electric motor

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	22.8	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	224	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	22.8	kW	$T_j=+35^\circ\text{C}$	$EER_d$	4.25	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	16.3	kW	$T_j=+30^\circ\text{C}$	$EER_d$	5.16	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	10.2	kW	$T_j=+25^\circ\text{C}$	$EER_d$	6.45	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	4.6	kW	$T_j=+20^\circ\text{C}$	$EER_d$	6.38	-

Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
---	----------	-----	---	--	--	--	--

### Power consumption in modes other than "active mode"

Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW

### Other items

Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	8950	$\text{m}^3/\text{h}$
Sound power level, indoors / outdoors	$L_{WA}$	-/73	dB				
Emissions of nitrogen oxides (if applicable)	$\text{NO}_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	$\text{m}^3/\text{h}$
GWP of the refrigerant	-	675	kg $\text{CO}_2$ eq (100years)				

Standard rating conditions used	Medium temperature application
Contact details	NØRDIS AC, Europe www.nordis-ac.com/

(\*) If  $C_{dc}$  is not determined by measurement then the default degradation coefficient of chillers shall be 0,9.  
(\*\*) From 26 September 2018.



# Information requirements for comfort chillers

Model(s):	MONO26WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	25.5	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	183	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	25.5	kW	$T_j=+35^\circ\text{C}$	$EER_d$	2.63	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	18.5	kW	$T_j=+30^\circ\text{C}$	$EER_d$	3.79	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	11.8	kW	$T_j=+25^\circ\text{C}$	$EER_d$	5.19	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	5.6	kW	$T_j=+20^\circ\text{C}$	$EER_d$	6.84	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	9750	m <sup>3</sup> /h
Sound power level, indoors / outdoors	$L_{WA}$	-/75	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m <sup>3</sup> /h
GWP of the refrigerant	-	675	kg CO <sub>2</sub> eq (100years)				
Standard rating conditions used	Low temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO26WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	26.8	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	226	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	26.8	kW	$T_j=+35^\circ\text{C}$	$EER_d$	4.04	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	19.4	kW	$T_j=+30^\circ\text{C}$	$EER_d$	5.21	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	12.1	kW	$T_j=+25^\circ\text{C}$	$EER_d$	6.23	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	5.9	kW	$T_j=+20^\circ\text{C}$	$EER_d$	6.94	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	9750	m <sup>3</sup> /h
Sound power level, indoors / outdoors	LWA	-/75	dB				
Emissions of nitrogen oxides (if applicable)	NO <sub>x</sub> (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m <sup>3</sup> /h
GWP of the refrigerant	-	675	kg CO <sub>2</sub> eq (100years)				
Standard rating conditions used	Medium temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO30WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	29.5	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	177	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	29.5	kW	$T_j=+35^\circ\text{C}$	$EER_d$	2.29	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	21.2	kW	$T_j=+30^\circ\text{C}$	$EER_d$	3.62	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	13.5	kW	$T_j=+25^\circ\text{C}$	$EER_d$	5.06	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	6.0	kW	$T_j=+20^\circ\text{C}$	$EER_d$	6.75	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	10650	m <sup>3</sup> /h
Sound power level, indoors / outdoors	LWA	-177	dB				
Emissions of nitrogen oxides (if applicable)	NO <sub>x</sub> (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m <sup>3</sup> /h
GWP of the refrigerant	-	675	kg CO <sub>2</sub> eq (100years)				
Standard rating conditions used	Low temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

# Information requirements for comfort chillers

Model(s):	MONO30WMONO3						
Outdoor side heat exchanger of chiller:	Air to water						
Indoor side heat exchanger chiller:	Water						
Type:	Compressor driven vapour compression						
Driver of compressor:	Electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	30.8	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	225	%
Declared cooling capacity for part load at given outdoor temperature $T_j$				Declared energy efficiency ratio for part load at given outdoor temperature $T_j$			
$T_j=+35^\circ\text{C}$	$P_{dc}$	30.8	kW	$T_j=+35^\circ\text{C}$	$EER_d$	3.79	-
$T_j=+30^\circ\text{C}$	$P_{dc}$	22.1	kW	$T_j=+30^\circ\text{C}$	$EER_d$	5.06	-
$T_j=+25^\circ\text{C}$	$P_{dc}$	13.9	kW	$T_j=+25^\circ\text{C}$	$EER_d$	6.33	-
$T_j=+20^\circ\text{C}$	$P_{dc}$	6.3	kW	$T_j=+20^\circ\text{C}$	$EER_d$	7.01	-
Degradation co-efficient for chillers (*)	$C_{dc}$	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	$P_{OFF}$	0.017	kW	Crankcase heater mode	$P_{CK}$	0.000	kW
Thermosat-off mode	$P_{TO}$	0.084	kW	Standby mode	$P_{SB}$	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	10650	m <sup>3</sup> /h
Sound power level, indoors / outdoors	LWA	-177	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x$ (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m <sup>3</sup> /h
GWP of the refrigerant	-	675	kg CO <sub>2</sub> eq (100years)				
Standard rating conditions used	Medium temperature application						
Contact details	NØRDIS AC, Europe www.nordis-ac.com/						
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient of chillers shall be 0,9. (**) From 26 September 2018.							

Model	Mode	Heating					Cooling	
	Ambient temperature	7/6			2/1	-7/-8	35/24	
	Water temperature	30-35	40-45	47-55	30-35	30-35	23-18	12-7
MONO18WMONO3	Capacity /W	18000	18000	18000	18000	18000	18500	17000
	Power input /W	3830	5143	6545	5325	6667	3895	5574
	COP / EER	4.70	3.50	2.75	3.38	2.70	4.75	3.05
MONO22WMONO3	Capacity /W	22000	22000	22000	22000	21000	23000	21000
	Power input /W	5000	6471	8302	7097	8077	5000	7119
	COP / EER	4.40	3.40	2.65	3.10	2.60	4.60	2.95
MONO26WMONO3	Capacity /W	26000	26000	26000	24000	22000	27000	26000
	Power input /W	6373	8387	10612	8333	8800	6279	9630
	COP / EER	4.08	3.10	2.45	2.88	2.50	4.30	2.70
MONO30WMONO3	Capacity /W	30100	30000	30000	26000	23000	31000	29500
	Power input /W	7698	10345	13043	9286	9388	7750	11569
	COP / EER	3.91	2.90	2.30	2.80	2.45	4.00	2.55

NOTE

---

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

NOTE

---

A series of horizontal dotted lines for writing notes.



16125300002402 V. B